

Name	SMG100								SMG200					
Model	12/12	12/24	24/12	24/24	24/48	48/12	48/24	48/48	12/12	12/24	24/12	24/24	24/48	48/12
Article no.														
Converter type	galvanic insulation and votage stabilizing								galvanic isolation and voltage stabilizing					
Input														
Nominal input voltage	12V	12V	24V	24V	24V	48V	48V	48V	12V	12V	24V	24V	24V	48V
Input range, full output specifications	9V..18V	9V..18V	20V..35V	20V..35V	20V..35V	30V..60V	30V..60V	30V..60V	9V..18V	9V..18V	20V..35V	20V..35V	20V..35V	30V..60V
Input range, no defects	0V..20V	0V..20V	0V..35V	0V..35V	0V..35V	0V..60V	0V..60V	0V..60V	0V..20V	0V..20V	0V..35V	0V..35V	0V..35V	0V..60V
Output														
Nominal output voltage	12.5V	24.5V	12.5V	24.5V	48V	12.5V	24.5V	48V	12.5V	24.5V	12.5V	24.5V	48V	12.5V
Voltage adjustment														
Stabilized													yes	
													1%	
Output voltage ripple, peakpeak													1%	
Maximum output power													200W	
Continue output power													100W	
Maximum output current	16A	8A	16A	8A	4A	16A	8A	4A	16A	8A	16A	8A	4A	16A
Continue output current	8A	4A	8A	4A	2A	8A	8A	4A	16A	8A	16A	8A	4A	16A
Continue output current at 40°C	8A	4A	8A	4A	2A	8A	8A	4A	16A	8A	16A	8A	4A	16A
General														
Efficiency													+/_87%	
No load consumption													+/_25mA	
Ambient operating temperature													-10°C .. +40°C, de-rating to 60°C	
Storage temperature													-25°C .. +85°C	
Operating humidity													95% max, non-condensing	
Galvanic insulation													yes	
Cooling fan													yes	
Protections														
Overcurrent / short circuit	limited by current sensing circuit to I-max								limited by current sensing circuit to I-max					
Over heat	yes								yes					
Features														
Microprocessor controlled													yes	
undervoltage													yes	
overvoltage													yes	
3 stage charger	yes with charger software												yes with charger software	
Programmable	yes												yes	
Smart undervoltage detection	Yes with charger software												Yes with charger software	
lithium ion charger	Yes with ion charger software												Yes with ion charger software	
Mechanical														
Connection input/output	Faston 6,3mm												Faston 6,3mm	
Dimensions (H*W*D)	50*151*88mm												50*175*88mm	
Mounting holes	dia 4mm 58*143mm												dia 4mm 58*168mm	
Weight	0,51Kg												0,59Kg	
cabinet	anodized aluminium black, ABS Blend end												anodized aluminium black, ABS Blend end cover	
Color	Black												Black	

Intellitec MV Ltd
Unit 9 Woodway Court
Thursby Road
Bromborough
Wirral CH62 3PR

Tel: 0151 482 8970

www.intellitecmv.com

Email: sales@intellitecmv.com



Name	SMG360									
Model	48/24	48/48	12/12	12/24	24/12	24/24	24/48	48/12	48/24	48/48
Article no.										
Converter type	galvanic isolation and voltage stabilizing									
Input										
Nominal input voltage	48V	48V	12V	12V	24V	24V	24V	48V	48V	48V
Input range, full output specifications	30V..60V	30V..60V	9V..18V	9V..18V	20V..35V	20V..35V	20V..35V	30V..60V	30V..60V	30V..60V
Input range, no defects	0V..60V	0V..60V	0V..20V	0V..20V	0V..35V	0V..35V	0V..35V	0V..60V	0V..60V	0V..60V
Output										
Nominal output voltage	24.5V	48V	12.5V	24.5V	12.5V	24.5V	48V	12.5V	24.5V	48V
Voltage adjustment							yes			
Stabilized							1%			
Output voltage ripple, peakpeak							1%			
Maximum output power							360W			
Continue output power							360W			
Maximum output current	8A	4A	30A	15A	30A	15A	8A	30A	15A	8A
Continue output current	8A	4A	30A	15A	30A	15A	8A	30A	15A	8A
Continue output current at 40°C	8A	4A	30A	15A	30A	15A	8A	30A	15A	8A
General										
Efficiency	+/_ 87%									
No load consumption	+/_ 25mA									
Ambient operating temperature	-10°C .. +40°C, de-rating to 60°C									
Storage temperature	-25°C .. +85°C									
Operating humidity	95% max, non-condensing									
Galvanic insulation	yes									
Cooling fan	Yes									
Protections										
Overcurrent / short circuit	limited by current sensing circuit to I-max									
Over heat	yes									
Features										
Microprocessor controlled	yes									
undervoltage	yes									
overvoltage	yes									
3 stage charger	yes with charger software									
Programmable	yes									
Smart undervoltage detection	Yes with charger software									
lithium ion charger	Yes with ion charger software									
Mechanical										
Connection input/output	Faston 6,3mm									
Dimensions (H*W*D)	83*190*133mm									
Mounting holes	dia 4mm 91*182mm									
Weight	1,37Kg									
cabinet	anodized aluminium blanc, ABS Blend end cover									
Color	Black									



SMG100

SMG200



SMG360

Intellitec MV Ltd
Unit 9 Woodway Court
Thursby Road
Bromborough
Wirral CH62 3PR

www.intellitecmv.com

Tel: 0151 482 8970 Email: sales@intellitecmv.com